
 SumiRiko Italy S.p.A.		<b>SumiRiko 3649 W 10 mm</b>					
<b>Power steering return hose</b>							
<b>Construction and material:</b>							
<b>Cover</b>	CM						
<b>Braid</b>	PET						
<b>tube</b>	CM						
<b>Hose dimension*:</b>							
<b>ID [mm]</b>	9.4 - 10.2						
<b>OD [mm]</b>	16.1 - 17.25						
<b>Concentricity [mm max]</b>	0,6						
<b>Mechanical characteristics:</b>							
<b>Max Working pressure [bar]</b>	25						
<b>Max Working temperature [C°]</b>	140 (peak 150)						
<b>Min Working temperature [C°]</b>	-40						
<b>Burst pressure resistance [bar]</b>	>170						
<b>Volumetric expansion</b>	5bar 2.5 cc/m    10bar 4.3 cc/m    15ba r5.7 cc/m						
<b>Adhesion</b>	>2.5 N/mm						
<b>Ozone resistance</b>	No cracks (72 h/ 100 ppcm at 40°)						
<b>Standard and :</b>							
<b>Product</b>	<b>Minimum batchs</b>		<b>Minimum lenghts</b>		<b>Preformed</b>	<b>x</b>	
<b>International standard</b>	<b>SAE 100 R6 (SAE J 517)</b>						
<b>Standard</b>	<b>MBN 10136 Mercedes - PTG</b>						
* eventuals request to discuss with the customer							